

MATERIAL SAFETY DATA SHEET

MSDS Name: WHITE MARKING PAINT
MSDS Number: 2900
Version Number 2
MSDS Date: NOV-27-2006
Page Number: 1 of 4

SECTION 1. PRODUCT AND COMPANY INFORMATION

Product Name: WHITE MARKING PAINT
CAS Number N/A
Hazard Rating: Health: 2 Fire: 0 Reactivity: 1 PPI:

Company Identification: DAMPNEY CO INC.
85 PARIS ST
EVERETT MA 02149-4411

Contact: CONRAD FOO
Telephone/Fax: (617) 389-2805 (617) 389-0484
Chemtrec (24 Hour): (800) 424-9300

Product Class INDUSTRIAL COATING
Trade Name WHITE MARKING PAINT
Product Code 2900

SECTION 2. INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
(No hazardous ingredients known at this time.)			

SECTION 3. PHYSICAL DATA

Form: LIQUID
Appearance/Color: WHITE
pH Value: 2.
Boiling Range: 0.°F
Melting Point: Not Applicable
Evaporation Rate: Non Volatile

Vapor Density:
Partition Coefficient Not Available
% Volatile Weight 0.%

MATERIAL SAFETY DATA SHEET

MSDS Name: WHITE MARKING PAINT
MSDS Number: 2900
Version Number: 2
MSDS Date: NOV-27-2006
Page Number: 2 of 4

% Volatile: 0.0%
Specific Gravity: 2.00
Weight/Gallon: 12.00 lbs
VOC: NONE
Heavy Elements (ppm): 0.

SECTION 4. FIRE AND EXPLOSION HAZARD DATA

Flammability Class: NONE
Flash Range: Not Applicable
Explosive Range: Not Applicable

EXTINGUISHING MEDIA:

N/A

SPECIAL FIREFIGHTING PROCEDURES:

N/A

UNUSUAL FIRE & EXPLOSION HAZARDS:

This material does not burn; however, it can react with metals to liberate hydrogen gas that can readily form flammable or explosive mixtures.

SECTION 5. HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

PERMISSIBLE EXPOSURE LEVEL:

SEE SECTION VIII

EFFECTS OF OVEREXPOSURE:

Causes burns to skin and eyes. Phosphoric acid may not produce an immediate burning sensation upon skin contact, delaying the awareness of the worker that contact has occurred. Following a 24 hour exposure, irreversible eye and skin damage occurred at all concentrations of phosphoric acid.

EMERGENCY AND FIRST AID PROCEDURES:

Ingestion: May cause nausea, vomiting, and diarrhea. Do not include vomiting. Immediately give large quantities of water. If vomiting occurs, give fluids again. Call a physician or the nearest poison center immediately.

MATERIAL SAFETY DATA SHEET

MSDS Name: WHITE MARKING PAINT
MSDS Number: 2900
Version Number 2
MSDS Date: NOV-27-2006
Page Number: 3 of 4

Skin contact: Immediately remove contaminated clothing under a safety shower. Flush affected areas with large amounts of water for at least 15 minutes. Do not attempt to neutralize with chemical agents. Obtain medical advice immediately.
Eye contact: Irritating; may cause chemical burns. Immediately flush the eyes with large quantities of water for at least 15 minutes. Hold the eyelids apart during flushing to ensure rinsing of the entire surface of the eye and lids with water. Obtain medical attention as soon as possible.

=====

SECTION 6. STABILITY AND REACTIVITY MEASURES

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Reacts with bases such as carbonates, oxides, and hydroxides of alkali metals. Forms hydrogen gas on reaction with metals.

=====

SECTION 7. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Contain spills and leaks to prevent discharge to the environment. Neutralize cautiously with a base such as soda ash. Keep product out of sewers, watersheds and water systems.
Small spills: Take up with absorbent material and place in non-leaking containers for proper disposal.

HIGHWAY OR RAILWAY SPILLS
CALL CHEMTREC (800) 424-9300

WASTE DISPOSAL METHOD:

Assure conformity with applicable federal, state and local regulations.

=====

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

RESPIRATORY PROTECTION:

MATERIAL SAFETY DATA SHEET

MSDS Name: WHITE MARKING PAINT
MSDS Number: 2900
Version Number 2
MSDS Date: NOV-27-2006
Page Number: 4 of 4

Use NIOSH approved respirator as required to prevent overexposure
VENTILATION:

Provide sufficient ventilation to keep air contaminant concentration below current applicable OSHA permissible exposure limit.

PROTECTIVE GLOVES:

Use chemical-resistant gloves to prevent skin contact.

EYE PROTECTION:

Use splash goggles or face shield to prevent eye contact.

OTHER PROTECTIVE EQUIPMENT:

Use chemical-resistant or other protective outerwear to protect against clothing contamination and skin contact.

SECTION 9. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING, TRANSPORTATION, AND STORING:

Storage and shipping containers should be plastic or type 316 stainless steel.

OTHER PRECAUTIONS:

Contact lenses pose a special hazard; soft lenses may absorb and all lenses concentrate irritants.

SECTION 10. REGULATORY INFORMATION

The information and recommendations contained herein are based on data believed to be correct. However, Dampney makes no warranty express or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or user to ensure that this material is properly and safely used.
